

### FEATURES

- 1/3" SONY Super HAD CCD II
- 420TVL IR ON 0lux
- IR distance 25M 24pcs  $\Phi$ 5 LED
- 3.6 or 6mm Lens
- IP66

### SPECIFICATIONS

<b>Model</b>	<b>SA-25A-36/SA-25A-60</b>
<b>Pick-up Device</b>	1/3"SONY Super HAD CCD II
<b>Scanning Area</b>	4.9mm(H) $\times$ 3.7mm(V)
<b>Picture Element</b>	PAL:500(H) $\times$ 582(V) NTSC:510(H) $\times$ 492(V)
<b>TV System</b>	PAL/NTSC
<b>Horizontal Resolution</b>	420TVL
<b>Illumination</b>	IR ON 0LUX
<b>S/N ratio</b>	More than 50dB
<b>Electronic Shutter</b>	PAL:1/50s-1/100,000s NTSC:1/60s-1/100,000s
<b>BLC</b>	Auto
<b>Synchronous System</b>	INT
<b>Video Output</b>	1.0Vp-p,75 $\Omega$ , BNC Connector
<b>Lens Mount</b>	3.6 or 6mm/M12
<b>Day/Night</b>	Pure color, Color to B&W
<b>IR Distance</b>	25m
<b>Operating Temperature</b>	-10 $^{\circ}$ C~+50 $^{\circ}$ C
<b>Voltage</b>	DC 12V $\pm$ 10%
<b>Power Consumption</b>	110mA (IR ON MAX 310mA)
<b>Measure</b>	L269*W84*H108
<b>Weight</b>	882g
<b>Material</b>	Aluminum alloy



*Strong bracket that hides and protects the cable*

