

### FEATURES

- 1/3"SONY Exview HAD CCD II
- 700TVL IR ON 0Lux
- Digital time lapse
- Lens : 4 or 6 mm
- IR 40M 39pcs Φ5
- Mechanical ICR D&N (Pure color, Color to B&W, Color to Color)

### SPECIFICATIONS

<b>Model</b>	<b>SA-40WIR-M</b>
<b>Pick-up Device</b>	1/3"SONY Exview HAD CCD II
<b>Scanning Area</b>	4.9mm(H)×3.7mm(V)
<b>Picture Element</b>	PAL:976(H)×582(V) NTSC:976(H)×494(V)
<b>TV System</b>	PAL/NTSC
<b>Horizontal Resolution</b>	700 TVL
<b>Min. Illumination</b>	IR ON 0 Lux
<b>S/N ratio</b>	More than 50dB
<b>Electronic Shutter</b>	PAL:1/50s-1/100,000s NTSC:1/60s-1/100,000s
<b>BLC</b>	Auto
<b>Synchronous System</b>	INT
<b>Video Output</b>	1.0Vp-p,75Ω, BNC Connector
<b>Lens Mount</b>	4 or 6 mm
<b>Day/Night</b>	Mechanical ICR D&N (Pure color, Color to B&W, Color to Color)
<b>IR Distance</b>	40m
<b>Operating Temperature</b>	-10°C~+50°C
<b>Voltage</b>	DC 12V±10%
<b>Power Consumption</b>	150mA (IR ON MAX 500mA)
<b>Measurements</b>	L311mm×W106mm×H135mm
<b>Weight</b>	1241g
<b>Material</b>	Aluminum alloy

*Has infrared cut to improve the image in daytime and night time*



*Strong brackets that hide and protect the cable*

